

A103 Oak Rustic Brushed & Matt Lacquered



Product Details

| | |
|-----------------|--|
| Product Code | A103 |
| Collection | Alpine Plank by V4 Wood Flooring |
| Construction | Engineered |
| Species | Oak |
| Product Type | Engineered Plank |
| Surface | Up to 6 coats |
| Finish | Satin Lacquered |
| Dimensions | 150 x 15/4 x 1900 |
| Total Thickness | 15 mm |
| Top Layer | 4 mm - Solid European Oak |
| Core Layer | 11 mm – 2 Layer Softwood |
| Grade | CD/ Rustic |
| Pack Size | 1.71 m ² |
| Pack Contents | 6 Boards – May Include 2 split lengths |
| Joint Type | Tongue & Grooved |
| Edge Profile | Bevel Edged on 4 sides |

Technical Information

| | |
|--|--|
| Country of Manufacture | China |
| EUTR/ European Timber Regulation | Full documented evidence of legality of timber |
| FSC® Certification | FSC® 100% Certification Available for Project Enquires |
| PEFC® Certification | Not available with this product |
| Janka Hardness | Oak 1360 lbf (6000N) |
| Slip Resistance | EN 1339 (test result USRV 100) |
| European Reaction to Fire Classification | EN 13501-1 (test result: Dn - S1) |
| Release of Formaldehyde | EN 717-1 (Test result < 0.012mg/m3) |
| Thermal Conductivity | EN 12524 (Test result: 0.16W/mK) |
| Tog Rating | 1.13 |

Grading CD/ Rustic

V4 Wood Flooring is chosen for its natural beauty, therefore grading criteria is always an approximation as every piece of timber is different. If further selection is needed please allow for extra material upon installation.

| | |
|------------------------------|---|
| Maximum Size of Sound Knots | 50 mm Diameter (approx') |
| Maximum Size of Filled Knots | 30 mm Diameter (approx') |
| Filled Defects | Allowed |
| Filler Type | Black and dark brown filler |
| Sap Wood | Allowed (few Sapwood at the corner allowed) |
| End Checks | Not Allowed |
| Heart Wood | Allowed |
| Insect Damage | Not Allowed |
| Colour Variation | Allowed |
| Small Shakes | Allowed |
| Ingrown Bark | Not Allowed |
| Grain Variation | Allowed |

Installation Methods

All V4 floors should be installed by experienced flooring installers who have read and understood the appropriate installation guides at www.v4woodflooring.co.uk

| | |
|-------------------------|---|
| Fully Bonded | Yes* |
| Secret Nailed | No |
| Floated on Underlay | Yes* |
| Over Underfloor Heating | Yes* (fully bonded installation recommended) |

Maintenance Schedule Advice

Avoid scratches by minimising grit and dust, install doorway entrance mats and felt pads to protect furniture. Use PH neutral cleaners and avoid soaking the floor with water. For more detailed advice visit www.v4woodflooring.co.uk

| Recommended Products | Initial | Regular | Monthly | Long Term |
|--|---------|---------|---------|-----------|
| Sweep/ Vacuum | √ | √ | | |
| Wood's Good Natural Floor Care Refresher | √ | | √ | |
| Wood's Good Natural Floor Care | | √ | | |
| Sanded and Re-lacquered | | | | √ |

