

# DC102

## Smokehouse Grey Oak Rustic Brushed, Stained & Hardwax Oiled



### Product Description

The Deco Collection comprises of six brand new colours created with a combination of traditional colouring techniques. The oak top layer is lightly brushed to form a relief of the natural grain. Then a coat of wood lye is hand applied to bleach the oak surface which reacts with the natural acids in the wood and bleaches the surface and prevents the oak from yellowing. The result is a textured surface to which layers of colour oil are applied to create deep lusted boards with a distinctive grain.

### Product Information

USAGE	Commercial and Residential Applications
Product Code	DC102
Name	DC102 Smokehouse Grey Oak Rustic Brushed, Stained & Hardwax Oiled
Dimensions	190 x 15 x 1900 mm
Board Type	Engineered, Multi-ply, Tongue & Groove
Pattern	1 Strip Micro Bevelled Plank
Pack Size	2.166m <sup>2</sup> (includes 6 boards with up to 2 random cut boards)
Top layer	4 mm Rustic European Oak
Timber Grade	CD Rustic Grade
Surface	Brushed & Hardwax Oiled
Suitable for Underfloor Heating	Yes (temperature of top face must not exceed 27°C /See fitting guide)
Guarantee	35 Year Domestic Guarantee (see website for details)
Commercial Guarantee	3 Year Commercial Guarantee (see website for details)

© This technical data sheet was written by V4 Woodflooring Ltd. Greenbays Park Carthouse Lane, Horsell, Surrey GU21 4YP. At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.

### Grading Criteria - CD Rustic

V4 Woodflooring is chosen for its natural beauty, therefore grading criteria is always an approximation as every piece of timber is different. If further selection is needed please allow for extra material upon installation.

Maximum Size of Sound Knots	50 mm Diameter (approx')
Maximum Size of Filled Knots	30 mm Diameter (approx')
Filled Defects	Allowed
Filler Type	Traditional Black and Dark Brown Filler
Sap Wood	Allowed
End Checks	Not Allowed
Heart Wood	Allowed
Insect Damage	Not Allowed
Colour Variation	Allowed
Small Shakes	Allowed
Ingrown Bark	Not Allowed
Grain Variation	Allowed

### General Data

Country of manufacture	China
European Timber Regulation	Full documented evidence of legality of timber
FSC®	FSC® 100% Certified
PEFC®	Not available with this product
JANKA HARDNESS RATING	Oak 1360 lbf (6000N)
SLIP RESISTANCE	Please enquire
EUROPEAN REACTION TO FIRE CLASSIFICATION	EN 13501-1 (test result: Dn - S1)
THERMAL CONDUCTIVITY	EN 12524 (Test result: 0.16W/mK)
RELEASE OF FORMALDEHYDE	EN 717-1 (Test result $\leq$ 0.012mg/m <sup>3</sup> )
STAIN RESISTANCE	(includes 6 boards with up to 2 random cut boards)
ACCOUSTIC PROPERTIES	Contact V4 Woodflooring Technical Department

© This technical data sheet was written by V4 Woodflooring Ltd. Greenbays Park Carthouse Lane, Horsell, Surrey GU21 4YP. At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.

### Installation Method

V4 Woodflooring® should be fitted in accordance with our installation guides by experienced flooring installers for more information visit [www.v4woodflooring.co.uk](http://www.v4woodflooring.co.uk).

Fully Bonded	Yes (Recommended)
Secret Nailed	No
Floated on Underlay	Yes
Over Underfloor heating	Yes (fully bonded recommended) Temperature of top surface should not exceed 27°C

### Cleaning & Maintenance - Domestic Schedule

Floors should be kept clean and free from dust and grit. It is recommended that high traffic areas and kitchen areas are given an initial application of Wood's Good Natural Floor Care Refresher.

**Note: Avoid soaking the floor with water. Use a Wood's Good Applicator Pad or a well wrung mop.**

RECOMMENDED PRODUCTS*	INITIAL	REGULAR	6 OR 12 MONTHLY (DEPENDING ON USE)
WOOD'S GOOD NATURAL CARE SOAP SPRAY		√	
WOOD'S GOOD NATURAL FLOOR CARE REFRESHER	√		√

\* Visit [www.v4woodflooring.co.uk](http://www.v4woodflooring.co.uk) for detailed advice on using the above products.

### Cleaning & Maintenance - Commercial Schedule

Floors should be kept clean and free from dust and grit. It is recommended that high traffic areas and kitchen areas are given an initial and regular application of Wood's Good Natural Floor Care Refresher.

**Note: Avoid soaking the floor with water. Use a Wood's Good Applicator Pad or a well wrung mop.**

RECOMMENDED PRODUCTS*	INITIAL	REGULAR	1 OR 6 MONTHLY (DEPENDING ON USE)
WOOD'S GOOD NATURAL CARE SOAP SPRAY OR WOOD'S GOOD NATURAL FLOOR CARE REFRESHER DILUTED		√	
WOOD'S GOOD NATURAL FLOOR CARE REFRESHER	√		√

\* Visit [www.v4woodflooring.co.uk](http://www.v4woodflooring.co.uk) for detailed advice on using the above products.