

EP104

Eiger Petit Engineered Collection

Oak Rustic Brushed, Grey Stained & Lacquered



Product Description

The 5mm rustic oak top layer is rolled with steel brushes to take away the softer grain whilst following the contours of the natural grain, the result is an enhanced surface texture which becomes tactile underfoot and extremely durable to everyday scratches. The brushed surface is further enhanced with a contemporary grey stain and protected by UV cured coats of Woods Good Lacquer.

Product Information

USAGE	Commercial and Residential Applications
Product Code	EP104
Name	EP104 Oak Rustic Brushed, Grey Stained & Lacquered
Dimensions	150 x 18 x Random mm
Board Type	3 ply Engineered hardwood board with tongue & groove profile
Pattern	5 mm CD grade rustic oak with micro bevelled edge on 4 sides
Pack Size	1.65m ² (Pack includes random cut boards ranging from 300 – 1500mm)
Top layer	Up to 6 coats of UV cured Wood's Good lacquer
Timber Grade	CD Rustic Grade
Surface	Brushed
Suitable for Underfloor Heating	Yes (temperature of top face must not exceed 27°C /See fitting guide)
Guarantee	35 Year Domestic Guarantee (see website for details)
Commercial Guarantee	3 Year Commercial Guarantee (see website for details)

© This technical data sheet was written by V4 Woodflooring Ltd. Greenbays Park Carthouse Lane, Horsell, Surrey GU21 4YP. At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.

Grading Criteria - CD Rustic

V4 Woodflooring is chosen for its natural beauty, therefore grading criteria is always an approximation as every piece of timber is different. If further selection is needed please allow for extra material upon installation.

Maximum Size of Sound Knots	50 mm Diameter (approx')
Maximum Size of Filled Knots	30 mm Diameter (approx')
Filled Defects	Allowed
Filler Type	Traditional Black and Dark Brown Filler
Sap Wood	Allowed
End Checks	Not Allowed
Heart Wood	Allowed
Insect Damage	Not Allowed
Colour Variation	Allowed
Small Shakes	Allowed
Ingrown Bark	Not Allowed
Grain Variation	Allowed

General Data

Country of manufacture	China
European Timber Regulation	Full documented evidence of legality of timber
FSC®	FSC® 100% Certification Available for Project Enquires
PEFC®	Not available with this product
JANKA HARDNESS RATING	Oak 1360 lbf (6000N)
SLIP RESISTANCE	EN 1339 (test result USRV 100)
EUROPEAN REACTION TO FIRE CLASSIFICATION	EN 13501-1 (test result: Dn - S1)
THERMAL CONDUCTIVITY	EN 12524 (Test result: 0.16W/mK)
RELEASE OF FORMALDEHYDE	EN 717-1 (Test result \leq 0.012mg/m3)
STAIN RESISTANCE	GOOD with correct care and maintenance
ACCOUSTIC PROPERTIES	Contact V4 Woodflooring Technical Department

© This technical data sheet was written by V4 Woodflooring Ltd. Greenbays Park Carthouse Lane, Horsell, Surrey GU21 4YP. At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.

Installation Method

V4 Woodflooring® should be fitted in accordance with our installation guides by experienced flooring installers for more information visit www.v4woodflooring.co.uk.

Fully Bonded	Yes (Recommended)
Secret Nailed	Yes
Floated on Underlay	Yes
Over Underfloor heating	Yes (fully bonded recommended) Temperature of top surface should not exceed 27°C

Cleaning & Maintenance - Domestic Schedule

Floors should be kept clean and free from dust and grit and furniture should be protected to avoid unnecessary wear and damage. All external doors should have mats to collect grit, fitted inside and out.

RECOMMENDED PRODUCTS*	REGULAR	MONTHLY	6 MONTHLY
WOOD'S GOOD LACQUER SOAP SPRAY	√		
WOOD'S GOOD LACQUER SOAP MOP APPLIED		√	
WOOD'S GOOD NATURAL FLOOR CARE REFRESHER			√

Cleaning & Maintenance - Commercial Schedule

Floors should be kept clean and free from dust and grit and furniture should be protected to avoid unnecessary wear and damage. All external doors should have mats to collect grit, fitted inside and out.

RECOMMENDED PRODUCTS*	REGULAR	MONTHLY	6 MONTHLY
WOOD'S GOOD LACQUER SOAP SPRAY			
WOOD'S GOOD LACQUER SOAP MOP APPLIED	√		
WOOD'S GOOD NATURAL FLOOR CARE REFRESHER		√	

* Visit www.v4woodflooring.co.uk for detailed advice on using the above products.