VIT109 - Oak Grey Rustic Brushed & Oiled





Product Details

i i oddot Botdiio				
Product Code	VIT109			
Collection	Vittoria by V4 Wood Flooring			
Construction	Engineered			
Species	Oak			
Product Type	Engineered Plank			
Surface	Brushed			
Finish	Grey UV Oiled			
Dimensions	190 x 14/3 x Random Length			
Total Thickness	14 mm			
Top Layer	3 mm - Solid European Oak			
Core Layer	11 mm – 2 Hardwood Ply			
Grade	CD/ Rustic			
Pack Size	2.508 m ²			
Pack Contents	Random Length Boards			
Joint Type	Tongue & Grooved			
Edge Profile	Bevel Edged on 4 sides			

Technical Information

Country of Manufacture	China			
EUTR/ European Timber Regulation	Full documented evidence of legality of timber			
FSC® Certification	Available for Project Enquires			
PEFC® Certification	Not available with this product			
Janka Hardness	Oak 1360 lbf (6000N)			
Slip Resistance	EN 1339 (test result USRV 100)			
European Reaction to Fire Classification	EN 13501-1 (test result: Dn - S1)			
Release of Formaldehyde	EN 717-1 (Test result < 0.012mg/m3)			
Thermal Conductivity	EN 12524 (Test result: 0.16W/mK)			
Tog Rating	1.12			

Grading CD/ Rustic

V4 Wood Flooring is chosen for its natural beauty, therefore grading criteria is always an approximation as every piece of timber is different. If further selection is needed please allow for extra material upon installation.

Maximum Size of Sound Knots	50 mm Diameter (approx')		
Maximum Size of Filled Knots	30 mm Diameter (approx')		
Filled Defects	Allowed		
Filler Type	Black and dark brown filler		
Sap Wood	Allowed (few Sapwood at the corner allowed)		
End Checks	Not Allowed		
Heart Wood	Allowed		
Insect Damage	Not Allowed		
Colour Variation	Allowed		
Small Shakes	Allowed		
Ingrown Bark	Not Allowed		
Grain Variation	Allowed		

Installation Methods

All V4 floors should be installed by experienced flooring installers who have read and understood the appropriate installation guides at www.v4woodflooring.co.uk

Fully Bonded	Yes*
Secret Nailed	No
Floated on Underlay	Yes*
Over Underfloor Heating	Yes* (fully bonded installation recommended)

Maintenance Schedule Advice

Avoid scratches by minimising grit and dust, install doorway entrance mats and felt pads to protect furniture. Use PH neutral cleaners and avoid soaking the floor with water. For more detailed advice visit www.v4woodflooring.co.uk

Recommended Products	Initial	Regular	Monthly	Long Term
Sweep/ Vacuum	√	√		
Wood's Good Natural Floor Care Refresher	√		√	
Wood's Good Natural Floor Care		√		
Maintenance oil				√



V4 Wood Flooring®

*Subject to correctly prepared and compatible subfloor and in conjunction with correct installation

Call +44(0)1276 488099 Email team@v4woodflooring.co.uk Visit www.v4woodflooring.co.uk © This technical data sheet was written by V4 Wood Flooring Ltd. Greenbays Park Carthouse Lane, Horsell, Surrey GU21 4YP. At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.