

DC102 Smokehouse Grey



Product Details

| | |
|-----------------|--|
| Product Code | DC102 |
| Collection | Deco Collection by V4 Wood Flooring |
| Construction | Engineered |
| Species | Oak |
| Product Type | Engineered Plank |
| Surface | Brushed, Stained |
| Finish | Hardwax Oiled |
| Dimensions | 190 x 15/4 x 1900 |
| Total Thickness | 15 mm |
| Top Layer | 4 mm - Solid European Oak |
| Core Layer | 11 mm - 2 Layer Softwood |
| Grade | CD/ Rustic |
| Pack Size | 2.166 m ² |
| Pack Contents | 6 Boards – May Include 2 split lengths |
| Joint Type | Tongue & Grooved |
| Edge Profile | Bevel Edged on 4 sides |

Technical Information

| | |
|--|--|
| Country of Manufacture | China |
| EUTR/ European Timber Regulation | Full documented evidence of legality of timber |
| FSC® Certification | FSC® 100% |
| PEFC® Certification | Not available with this product |
| Janka Hardness | Oak 1360 lbf (6000N) |
| Slip Resistance | Contact V4 Customer Support |
| European Reaction to Fire Classification | EN 13501-1 (test result: Dn - S1) |
| Release of Formaldehyde | EN 717-1 (Test result < 0.012mg/m3) |
| Thermal Conductivity | Contact V4 Customer Support |
| Tog Rating | 1.13 |

V4 Wood Flooring is chosen for its natural beauty, therefore grading criteria is always an approximation as every piece of timber is different. If further selection is needed please allow for extra material upon installation.

| | |
|------------------------------|---|
| Maximum Size of Sound Knots | 50 mm Diameter (approx') |
| Maximum Size of Filled Knots | 30 mm Diameter (approx') |
| Filled Defects | Allowed |
| Filler Type | Black and dark brown filler |
| Sap Wood | Allowed (few Sapwood at the corner allowed) |
| End Checks | Not Allowed |
| Heart Wood | Allowed |
| Insect Damage | Not Allowed |
| Colour Variation | Allowed |
| Small Shakes | Allowed |
| Ingrown Bark | Not Allowed |
| Grain Variation | Allowed |

Installation Methods

All V4 floors should be installed by experienced flooring installers who have read and understood the appropriate installation guides at www.v4woodflooring.co.uk

| | |
|-------------------------|---|
| Fully Bonded | Yes* |
| Secret Nailed | No |
| Floated on Underlay | Yes |
| Over Underfloor Heating | Yes* (fully bonded installation recommended) |

Maintenance Schedule Advice

Avoid scratches by minimising grit and dust, install doorway entrance mats and felt pads to protect furniture. Use PH neutral cleaners and avoid soaking the floor with water. For more detailed advice visit www.v4woodflooring.co.uk

| Recommended Products | Initial | Regular | Monthly | Long Term |
|--|---------|---------|---------|-----------|
| Sweep/ Vacuum | ✓ | ✓ | | |
| Wood's Good Natural Floor Care Refresher | ✓ | | ✓ | |
| Wood's Good Natural Floor Care | | ✓ | | |
| Maintenance Oil | | | | ✓ |



The mark of responsible forestry



Grading CD/ Rustic

V4 Wood Flooring®

Call +44(0)1276 488099
Email team@v4woodflooring.co.uk
Visit www.v4woodflooring.co.uk

*Subject to correctly prepared and compatible subfloor and in conjunction with correct installation

© This technical data sheet was written by V4 Wood Flooring Ltd. Greenbays Park Carthouse Lane, Horsell, Surrey GU21 4YP. At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.