

DC101 Frozen Umber Oak Rustic Brushed Stained & Hardwax Oil



D.	20	ы	0.0	ct	\Box	~ 1	ŀai	
П	U	u	u	Uι	\boldsymbol{L}	ᄕ	Lai	15

DC101		
Deco		
Engineered		
Oak		
Engineered Plank		
Brushed & Stained		
Hardwax Oil		
190 x 15/4 x 1900 mm		
4 mm - Solid European Oak		
11 mm – Multi Layer Eucalyptus & Poplar		
Rustic		
2.166 m ²		
6 Boards – May Include 2 split lengths		
Tongue & Grooved		
Bevel Edged on 4 sides		

Technical Information

Country of Manufacture	China		
EUTR/ European Timber Regulation	Full documented evidence of legality of timber		

FSC® Certification	FSC®100% (TT-COC-004200)
PEFC® Certification	Not available with this product
Janka Hardness	Oak 1360 lbf (6000N)
Slip Resistance	EN 14231 (Test Result 62/28 PTV)
European Reaction to Fire Classification	EN 13501-1 (test result Dfl-s1)
Release of Formaldehyde	EN 717-1 (Test result E1)
Thermal Conductivity	EN 12524 (Test result: 0.16W/mK)
Tog Rating	1.13

Grading: Rustic

Rustic Floors can contain varying size live and filled dead knots. Colour variation, sapwood, heartwood and end-checks (filled splits).

V4 Wood Flooring is chosen for its natural beauty, therefore grading criteria is always an approximation as every piece of timber is different. If further selection is needed please allow for extra material upon installation.

Installation Methods

All V4 floors should be installed by experienced flooring installers who have read and understood the appropriate installation guides at www.v4woodflooring.co.uk

Fully Bonded	Yes*		
Secret Nailed	No		
Floated on Underlay	Yes*		
Over Underfloor Heating	Yes* (fully bonded installation recommended)		

Maintenance Schedule Advice

Avoid scratches by minimising grit and dust, install doorway entrance mats and felt pads to protect furniture. Use PH neutral cleaners and avoid soaking the floor with water. For more detailed advice visit www.v4woodflooring.co.uk





V4 Wood Flooring®

*Subject to correctly prepared and compatible subfloor and in conjunction with correct installation

Call +44(0)1276 488099 Email team@v4woodflooring.co.uk Visit www.v4woodflooring.co.uk © This technical data sheet was written by V4 Wood Flooring Ltd. Greenbays Park Carthouse Lane, Horsell, Surrey GU21 4YP. At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.