



FSC® Certification	Not available with this product
PEFC® Certification	PEFC® Certified
Slip Resistance	Please enquire at technical@v4woodflooring.co.uk
European Reaction to Fire Classification	Dfl – s 1
Release of Formaldehyde	EN 717-1 (Test result E1)
Thermal Conductivity	EN 12524 (Test result: 0.147W/mK)
Tog Rating	1.21

Grading: Rustic

Rustic Floors can contain varying size live and filled dead knots. Colour variation, sapwood, heartwood and end-checks (filled splits).

V4 Wood Flooring is chosen for its natural beauty, therefore grading criteria is always an approximation as every piece of timber is different. If further selection is needed, please allow for extra material upon installation.

Installation Methods

All V4 floors should be installed by experienced flooring installers who have read and understood the appropriate installation guides at www.v4woodflooring.co.uk

Fully Bonded	Yes*
Secret Nailed	No
Floated on Underlay	Yes*
Over Underfloor Heating	Yes* (fully bonded installation recommended)

Maintenance Schedule Advice

Avoid scratches by minimising grit and dust, install doorway entrance mats and felt pads to protect furniture. Use PH neutral cleaners and avoid soaking the floor with water. For more detailed advice visit www.v4woodflooring.co.uk

Product Details

Product Code	EQ105
Collection	Equilibrium
Construction	Engineered
Species	European Walnut
Product Type	Engineered Plank
Surface	Hand Planed, Stained & Lacquered
Finish	Lacquered
Dimensions	500 x 20/5 x 1800 - 2800 mm
Top Layer	5 mm – Solid European Walnut
Core Layer	Softwood core with 5 mm Walnut base layer
Grade	Rustic
Pack Size	Wrapped
Pack Contents	N/A
Joint Type	Tongue & Grooved
Edge Profile	Bevel Edged on 2 sides

Technical Information

Country of Manufacture	Italy
EUTR/ European Timber Regulation	Full documented evidence of legality of timber

