

UN103 Weathered Beam Oak Rustic Embossed Stained & Hardwax Oil



Pro	du	ct	De	ta	ils

Product Code	UN103
Collection	Urban Nature
Construction	Engineered
Species	Oak
Product Type	Engineered Plank
Surface	Embossed, Stained & Deep Filled Splits
Finish	Hardwax Oil
Dimensions	190 x 15/4 x 1900 mm
Top Layer	4 mm - Solid European Oak
Core Layer	11 mm – Multi Layer Eucalyptus & Poplar
Grade	Rustic
Pack Size	2.166 m ²
Pack Contents	6 Boards – May Include 2 split lengths
Joint Type	Tongue & Grooved
Edge Profile	Bevel Edged on 4 sides

Technical Information

Country of Manufacture	China		
EUTR/ European Timber Regulation	Full documented evidence of legality of timber		

FSC® Certification	FSC®100% (TT-COC-004200)
PEFC® Certification	Not available with this product
Janka Hardness	Oak 1360 lbf (6000N)
Slip Resistance	EN 14231 (Test Result 68/30 PTV)
European Reaction to Fire Classification	EN 13501-1 (test result Dfl-s1)
Release of Formaldehyde	EN 717-1 (Test result E1)
Thermal Conductivity	EN 12524 (Test result: 0.16W/mK)
Tog Rating	1 13

Grading: Rustic

Rustic Floors can contain varying size live and filled dead knots. Colour variation, sapwood, heartwood and end-checks (filled splits).

V4 Wood Flooring is chosen for its natural beauty, therefore grading criteria is always an approximation as every piece of timber is different. If further selection is needed please allow for extra material upon installation.

Installation Methods

All V4 floors should be installed by experienced flooring installers who have read and understood the appropriate installation guides at www.v4woodflooring.co.uk

Fully Bonded	Yes*
Secret Nailed	No
Floated on Underlay	Yes*
Over Underfloor Heating	Yes* (fully bonded installation recommended)

Maintenance Schedule Advice

Avoid scratches by minimising grit and dust, install doorway entrance mats and felt pads to protect furniture. Use PH neutral cleaners and avoid soaking the floor with water. For more detailed advice visit www.v4woodflooring.co.uk





V4 Wood Flooring®

*Subject to correctly prepared and compatible subfloor and in conjunction with correct installation