

# ZBL305 Oak Rustic Brushed & Lacquer



#### **Product Details**

1 Toddot Dotallo	
Product Code	ZBL305
Collection	ZigZag Lock
Construction	Engineered
Species	Oak
Product Type	Engineered Parquet Block
Surface	Brushed & Stained
Finish	Lacquer
Dimensions	130 x 14/2.5 x 725 mm
Top Layer	2.5 mm - Solid European Oak
Core Layer	11.5 mm – Cross constructed Coniferous Wood
Grade	Rustic
Pack Size	0.65m²
Pack Contents	7 Boards
Joint Type	Click system
Edge Profile	Bevel Edged on 4 sides

#### **Technical Information**

Country of Manufacture	Poland
EUTR/ European Timber Regulation	Product made in the EU
FSC® Certification	Certification Available for Project Enquiries
PEFC® Certification	Not available with this product
Janka Hardness	Oak 1360 lbf (6000N)
Slip Resistance	NPD
European Reaction to Fire Classification	EN 14342:2013 (test result Dfl-s1)
Release of Formaldehyde	EN 14342:2013 (Test result E1)
Thermal Conductivity	EN 14342:2013 (Test result: 0.14W/mK)
Tog Rating	1.13

# **Grading: Rustic**

Rustic Floors can contain varying size live and filled dead knots. Colour variation, sapwood, heartwood and end-checks (filled splits).

V4 Wood Flooring is chosen for its natural beauty, therefore grading criteria is always an approximation as every piece of timber is different. If further selection is needed, please allow for extra material upon installation.

### **Installation Methods**

All V4 floors should be installed by experienced flooring installers who have read and understood the appropriate installation guides at www.v4woodflooring.co.uk

Fully Bonded	Yes, + bond header joints with D3 adhesive
Secret Nailed	No
Floated on Underlay	No
Over Underfloor Heating	Yes* (fully bonded installation recommended)

# **Maintenance Schedule Advice**

Avoid scratches by minimising grit and dust, install doorway entrance mats and felt pads to protect furniture. Use PH neutral cleaners and avoid soaking the floor with water. For more detailed advice visit www.v4woodflooring.co.uk



# V4 Wood Flooring®

\*Subject to correctly prepared and compatible subfloor and in conjunction with correct installation